

# Matlab code for BLO-OMP

Wenjing Liao and Albert Fannjiang

March 17, 2014

## 1 Spectral estimation

The package contains the codes of Orthogonal Matching Pursuit (OMP) and Band-excluded and Locally Optimized OMP (BLO-OMP) for the spectral estimation problem:

$$y_k = \sum_{j=1}^s x_j e^{-2\pi i k \omega_j} + e_k,$$

where  $\omega_j \in [0, 1)$ ,  $x_j \in \mathbb{C}$ ,  $k = -f_c, \dots, f_c$  and  $e \sim N(0, \sigma^2 I) + iN(0, \sigma^2 I)$ .

## 2 Functions

1. **Main:** the main function where frequencies and measurements are generated.
2. **OMP:** the code of realizing OMP [2].
3. **BLOOMP:** the code of realizing BLO-OMP [1].
4. **H\_dist:** the code of computing the Hausdorff distance between two frequency support set. For example, let  $\mathcal{S} = \{\omega_j\}$  and  $\hat{\mathcal{S}} = \{\hat{\omega}_j\}$ . The Hausdorff distance between  $\mathcal{S}$  and  $\hat{\mathcal{S}}$  is

$$d(\hat{\mathcal{S}}, \mathcal{S}) = \max \left\{ \max_{\hat{\omega} \in \hat{\mathcal{S}}} \min_{\omega \in \mathcal{S}} d(\hat{\omega}, \omega), \max_{\omega \in \mathcal{S}} \min_{\hat{\omega} \in \hat{\mathcal{S}}} d(\hat{\omega}, \omega) \right\}.$$

where  $d(\omega, \hat{\omega})$  is the distance between  $\omega$  and  $\hat{\omega}$  on Torus.

## References

- [1] A. Fannjiang, and W. Liao, "Coherence pattern-guided compressive sensing with unresolved grids," *SIAM Journal on Imaging Sciences* **5(1)** pp.179-202, 2012.
- [2] Y. C. Pati, R. Rezaeiifar and P. S. Krishnaprasad, "Orthogonal matching pursuit: Recursive function approximation with applications to wavelet decomposition," *The Twenty-Seventh Asilomar Conference on Signals, Systems and Computers, IEEE*, 1993.